

## DATA SHEET

## **CI865** ABB Ability™ System 800xA® hardware selector



The CI865 module is the AC 800M system's communication interface for Satt ControlNet and bridges different bus standards used on AC 800M and Satt ControlNet. The CI865 module makes it possible to use older Satt I/O system (Rack I/O and Series 200 I/O) with the AC 800M controller platform, but it cannot be used as a general ControlNet interface. CI865 cannot be used in a High Integrity controller.

## Features and benefits

- Satt 19 inch rack I/O, a rack-based I/O system, can be connected to AC 800M using the CI865 interface module
- CI865 supports online replacement (Hot Swap), and does not require any configuration before installation
- The CI865 unit handles I/O scanning of up to 31 distributed I/O systems

| General info                     |                |  |
|----------------------------------|----------------|--|
| Article number                   | 3BSE040795R1   |  |
| Communication protocol           | ABB's Satt I/O |  |
| Master or slave                  | Master         |  |
| Transmission speed               | -              |  |
| Line redundancy                  | No             |  |
| Module redundancy                | No             |  |
| Hot Swap                         | Yes            |  |
| Used together with HI Controller | No             |  |

| Detailed data         |            |  |
|-----------------------|------------|--|
| Max units on CEX bus  | 4          |  |
| Connector             | BNC        |  |
| 24 V consumption typ. | typ 120 mA |  |

| Environment and certification |                                      |
|-------------------------------|--------------------------------------|
| Temperature, Operating        | +5 to +55 °C (+41 to +131 °F)        |
| Temperature, Storage          | -40 to +70 °C (-40 to +158 °F)       |
| Corrosion protection          | G3 compliant to ISA 71.04            |
| Protection class              | IP20 according to EN60529, IEC 529   |
| CE- marking                   | Yes                                  |
| RoHS compliance               | DIRECTIVE/2011/65/EU (EN 50581:2012) |
| WEEE compliance               | DIRECTIVE/2012/19/EU                 |

| Dimensions              |                    |
|-------------------------|--------------------|
| Width                   | 59 mm (2.3 in.)    |
| Height                  | 185 mm (7.3 in.)   |
| Depth                   | 127.5 mm (5.0 in.) |
| Weight (including base) | 700 g (1.5 lbs)    |



solutions.abb/800xA solutions.abb/controlsystems

## \_

800xA and Symphony Plus is a registered trademark of ABB. All rights to other trademarks reside with their respective owners.

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document. We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2024 ABB All rights reserved