

DATA SHEET

## **CI871A**

## ABB Ability™ System 800xA® hardware selector



The CI871A is an AC 800M communication interface that connects to the PROFINET IO devices through Ethernet. The TP867 Baseplate has two RJ45 Ethernet connectors, but only the CH1 connector that supports 100Mbps is used for PROFINET IO connection. The Ethernet cable must be connected to the PROFINET IO network through an Ethernet switch.

The CI871 expansion unit contains the CEX-Bus logic, a communication unit, and a DC/DC converter that supplies the required voltage from +24 V supply through the CEX-Bus.

The CI871A module will only work with System 800xA 6.0.3.3, 6.1.1 and subsequent versions  $\,$ 

## **Features and benefits**

Connects PROFINETIO devices through Ethernet

General info		
Article number	3BSE092693R1	
Communication protocol	PROFINET IO	
Master or slave	Master	
Transmission speed	10/100 Mbit/s	
Line redundancy	No	
Module redundancy	Yes	
Hot Swap	Yes	
Used together with HI Controller	Yes	

Detailed data	
Max units on CEX bus	12
Connector	RJ-45 female (8-pin)
24 V consumption typ.	typ 160 mA

Environment and certification		
+5 to +55 °C (+41 to +131 °F)		
-40 to +70 °C (-40 to +158 °F)		
2000 m according to IEC/EN 61131-2		
Degree 2 according to IEC/EN 61131-2		
G3 compliant to ISA 71.04		
5 to 95 %, non-condensing		
IP20 according to EN60529, IEC 529		
Yes		
UL 61010-1, UL 61010-2-201		
UL 60079-15, cULus Class 1, Zone 2, AEx nA IIC T4, ExnA IIC T4Gc X		
DNV-GL, (Pending: ABS, BV, LR)		
DIRECTIVE/2011/65/EU (EN 50581:2012)		
DIRECTIVE/2012/19/EU		

Dimensions	
Width	59 mm (2.3 in.)
Height	185 mm (7.3 in.)
Depth	127.5 mm (5.0 in.)
Weight (including base)	700 g (1.5 lbs)



solutions.abb/800xA solutions.abb/controlsystems

800xA and Symphony Plus is a registered trademark of ABB. All rights to other trademarks reside with their respective owners.

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2024 ABB All rights reserved